

STEP UP TO BAJAJ QUTE. INTRODUCING THE SMART TAXI.



Smart Mileage
36 kmpl*



Smart Maneuverability
3.5 m turning radius



Smart Protection
Monocoque body



Smart Eco-friendly
40% lower CO₂ emission



TECHNICAL SPECIFICATIONS

DESCRIPTION		WHEELS AND TYRES	
ENGINE Capacity Max. Engine Output Max. Torque	Four stroke, Twin spark-ignition, Single cylinder engine, liquid cooled 216.6 cm ³ 9.9 Kw at 5500 19.6 Nm at 4000	Front	135/70R12 (Radial Tubeless)
		Rear	135/70R12 (Radial Tubeless)
		Spare	135/70R12 (Radial Tubeless)
		BODY	Steel monocoque body made in high strength steel
CLUTCH	Wet Multi-Disc Clutch	WEIGHTS (KG) Unladen Mass 449 Kgs Gross vehicle weight 749 Kgs Payload 300 Kgs	
TRANSMISSION	Constant Mesh Manual, 5 forward & 1 reverse		
FUEL TANK	8 liters (nominal) Petrol		
PERFORMANCE Max. speed 70 km/h, 5th Gear Max. Gradability 20% (11.30 degree) in first gear		SEATING CAPACITY 4, including driver	
SUSPENSION Front Rear	Independent Suspension with Twin leading arm, coil over shock absorber & anti roll bar Independent suspension with Semi trailing arm and coil over shock absorber	ELECTRICAL SYSTEMS Battery 12V, 26AH Engine management ECU, Fuel injected Head lamp 60 X 55W HS1 Tail/Stop lamp 5/21W	
		MAIN CHASSIS DIMENSIONS (IN MM) Overall height (Unladen) 1652 Overall length 2752 Wheel Base 1925 Rear overhang 440 Overall width 1312 Wheel track 1143 Lowest Hard Point From Ground 180 – Unladen Lowest Hard Point From Ground 180 - Unladen Turning circle radius 3.5 meters	
STEERING	Manual (Rack & Pinion)		
BRAKES Parking Brakes	Hydraulic with H-split. All Drum, Dia 180 mm. Right Foot operated control Mechanical (cable operated) Hand operated, Rear wheel	** Specifications mentioned above are subject to change.	